

PH-855 Digital Video Doorphone System

- >CE approval (PH-855 System)
- >Simple wiring & easy installation
- >4 wires + video cable + 2 power wires
- >Stainless steel material and unique backlight keypad in camera, dark automatic auxiliary illumination, let you have a clear view in the dark night.
- >Store 500 open door codes in camera and code range from 1-12 digit. You can also store resident's name by English letters.
- >European style design.
- >Several languages for supporting different countries demand-French, German, Spanish, Portuguese, Polish, Czech, Danish & English.
- >External connect a LCD Panel with the 855CC so as the Guard can view all the Visitors
- >Utilizing the latest CPU controlled technology and the intelligent interface module such as 855CSD,855VSB and etc to make the system more efficient and easy to operate
- >3 kinds of power supplies AC90-250V input or DC IN
- >Audio handset (PH-855M3, Md or Mg) is also available
- >Audio / Video doorbell (PH-855C3, C12a or C12b) unit
- >Group Intercom all monitors in monitor function.



PH-855C8 Stainless Steel Digital Camera with card reader

Power In: DC15~18V by Adaptor
Resolution: Color- 480 TV line
Lens: Auto
CCD: 1/3" Color CCD
 F1.8/3.6mm,Full angle 92 Degree
Min. illumination: 0.1Lux at 4 white LEDs
Material: Stainless Steel
Dimensions: 300x200x75mm
Packing:0.25 cubic ft
Weight: 2.9 kgs
 Need Prebox
 with Inductive Card Reader
 Editing by remote control system
 Memorize 2,500 pcs Inductive Cards (EM/ Mifare Card)
 Stainless steel+ Back light Keypad



SUS316
Stainless Steel

PH-855C7 Stainless Steel Digital Camera

[Flash Demo of PH-855C7](#)
Power In: DC15~18V by Adaptor
Resolution: Color- 480 TV line
Lens: Auto
CCD: 1/3" Color CCD
 F1.8/3.6mm,Full angle 92 Degree
Min. illumination: 0.1Lux at 4 white LEDs
Material: Stainless Steel
Dimensions:
W/prebox: 325x120x80mm (w/flush mounting prebox)
W/O prebox: 325x120x60mm
Packing:0.13 cubic ft
Weight: 1.5 kg
 Need Prebox
 Front panel+inner box+ keypad: SUS304
 Back light Keypad
 500 password for door open code
 European Style + Memory your name in Camera



SUS304
Stainless Steel

PH-855C9 CCD Push Button Camera with Card Reader

12 to 24 Residents are Available
Power In: DC15~18V by Adaptor
Resolution: Color- 480 TV line
Lens: Auto
CCD: 1/3" Color CCD
 F1.8/3.6mm,Full angle 92 Degree
Min. illumination: 0.1Lux at 4 white LEDs
Material: Stainless Steel
Dimensions: 300x200x75mm
Packing: 0.25 cubic ft
Weight: 2.9 kgs
 Need Prebox
 with Inductive Card Reader
 Editing by remote control system
 Memorize 2,500 pcs Inductive Cards (EM/ Mifare Card)
 Stainless steel Panel



Stainless Steel

PH-855C10AL Aluminum Camera

1 to 2 Residents are Available
Power In: DC15~18V by PH-P7a
Resolution: Color- 480 TV line
Lens: Auto
CCD: 1/3" Color CCD
 F1.8 / 3.6mm,Full angle 92 Degree
Min. illumination: 0.1Lux at 4 white LEDs
Material: Aluminum
Dimensions: 240X120X60mm
Packing: 0.4 cubic ft
Weight: 0.8 kg
 Need Prebox (Surface or flash Type)
 Aluminum case, Back light name plate



PH-855C5 10 Buttons Digital Camera

1 to 10 Residents are Available
Power In: DC15~18V by Ph-P7a
Resolution: Colour- 480 TV line
Lens: Auto
CCD: 1/3" Colour or B/W CCD
 F1.8/3.6mm,Full angle 92 Degree
Min. illumination: 0.1Lux at 4 white LEDs
Dimension:
W/prebox: 325x120x80mm (w/flush mounting prebox) ,325x120x85mm (w/surface mounting prebox)

PH-855K2 20-Button keyboard

1 to 20 Residents are Available
Working Voltage: From 368C5
Installation way: Flush mounting type or Surface mounting type
Front Panel: Alum
Dimensions: (L)323mm/(W)120mm/(H)55mm
 Flush part 45mm, the thickness after installation is 10mm
Weights: 0.4 kg
Measurement: 0.13'
Dimensions of flush pre-box: material-zinc



W/O prebox: 325x120x60mm
 Packing: 0.13 cubic ft
 Weight: 1.5 kg
 Need Prebox



plate
 Flush pre-box:
 (L)290mm/(W)100mm/(H)55mm
 Surface pre-box:
 (L)323mm/(W)120mm/(H)55mm
 Double pre-chassis:
 (L)323mm/(W)270mm/(H)45mm
 Double Surface pre-box:
 (L)323mm/270mm/(H)45mm

Front Panel: Alum
 Inner box: SUS316
 stainless steel

PH-855C15 CCD Push Button Camera with Card Reader

Power In: DC15~18V by Adaptor
 Resolution: Color- 480 TV line
 Lens: Auto
 CCD: 1/3" Color CCD
 F1.8/3.6mm, Full angle 92 Degree
 Min. illumination: 0.1Lux at 4 white LEDs
 Material: ABS
 one button on it for single house or call Guard
 Dimension: 285x100x40mm
 Packing: 0.13 cubic ft
 Weight: 1.0 kg
 Wall mounting type
 Flush mounting type--No need extra pre-box,
 just put the base into the wall directly
 with Inductive Card Reader
 Editing by remote control system
 Memorize 2,500 pcs Inductive Cards (EM/
 Mifare Card)



PH-855K3 8-Button keyboard

1 to 8 Residents are Available
 Power In: Supply from PH-855C15
 LED illumination display
 Material: ABS
 Dimension: 285x50x40mm
 Packing: 0.08 cubic ft
 Weight: 0.6 kg
 Wall mounting type
 Flush mounting type--No need extra pre-box,
 just put the base into the wall directly



PH-855C6 phasid out with metal digital keypad

Password door open function is available
 Resolution: Colour-480 TV lines
 Lens: Auto
 CCD: 1/3" Color CCD
 F1.8, Full angle 92°
 Min. illumination: 0.1Lux at 4 white LEDs
 Material: Aluminum
 Dimension: 300/200/75mm
 Packing: 0.25 cubic ft
 Weight: 2.7 kgs



PH-855C10 phasid out Stainless steel CCD Camera

1 to 4 Residents are Available
 Power In: DC15~18V by PH-P7
 Touch Pad keyboard
 Resolution: Color- 480 TV line
 Lens: Pinhole Lens, Auto
 CCD: 1/3" Colour or B/W CCD
 Min. illumination: 0.1Lux at 4 white LEDs
 Material: Stainless Steel
 Dimensions: 100x180x30mm
 Packing: 0.06 cubic ft
 Weight: 1.0 kg
 Wall mounting type (no need Prebox)
 SUS304 Stainless steel case
 Need rain cover of outdoor status



PH-855C12a phasid out CCD Camera


1 Resident is Available
 Power In: DC15~18V by PH-P7a
 Resolution: Color- 480 TV line
 Lens: Pinhole Lens, Auto
 CCD: 1/3" Color CCD
 Min. illumination: 2Lux
 Material: Stainless Steel
 Dimensions: 230x150x2(47)mm
 Packing: 0.06 cubic ft
 Weight: 1.0 kg
 Need Prebox (Flush Type)
 Stainless steel case
 Need rain cover of outdoor status



Pinhole Type

PH-855C12b phasid out CCD Camera

1 Resident is Available
 Power In: DC15~18V by PH-P7a
 Resolution: Color- 480 TV line
 Lens: Pinhole Lens, Auto
 CCD: 1/3" Color CCD
 Min. illumination: 0.1Lux at 4 white LEDs
 Material: Stainless Steel
 Dimensions: 230x150x2(47)mm
 Packing: 0.06 cubic ft
 Weight: 1.0 kg
 Need Prebox (Flush Type)
 Stainless steel case
 Need rain cover of outdoor status



Pinhole Type

PH-855C3AL Door bell with CCD

Power In: supply From M
 Resident Door bell
 wire: 4 (with CCD)
 Resolution: Color- 480 TV line
 Lens: Auto
 CCD: 1/3" Color F1.8, 92 degrees
 Min. illumination: 0.1Lux at 4 white LEDs
 Material: Aluminum
 Dimensions: 240X120X60mm
 Packing: 0.06 cubic ft
 Weight: 1.0 kg
 Need Prebox (Flush or surface Type)



PH-855C11 Door Bell with CCD

Power In: supply from M
 Resident Door bell
 wire: 4 (with CCD)
 Resolution: Color- 480 TV line
 Lens: Auto
 CCD: 1/3" CCD F1.8, 92 degrees
 Min. illumination: 0.1Lux at 4 white LEDs
 Material: ABS
 Dimension: 80/125/32mm
 Packing: 0.2 cubic ft
 Weight: 0.2 kg



PH-855MmR 8" Handsfree LED color Monitor w/ Video Recorder

Video Handsfree Monitor
 Power In: DC15V
 Screen: Color- 8" LED Color LCD Panel
 Brightness: 250 nix (or cd/m2), new vivid saturation color
 Resolution: 800 RGB(W) x 600(H) dot
 Active Area: 162(W) x 121.5(H) mm
 Color configuration: R. G. B. stripe
 View Angle: Top: 50deg. Bottom: 65deg.
 left / Right: 65deg



phase out

Calling tone: Ding-Dong tone
Consumption: standby 260mA, operating 650mA
Wall mounting type
Material: ABS
wire: 4 wires + 2 power wires + 1 Video cable
Dimension: 212W/201H/40T mm
Packing: 0.18 cubic ft
Weight: 1.0 kg

Video Recorder

Video recorded with a device that is compatible with MPEG-4.(Linux format)
Resolution : 640*480 30FPS per second
Memory Card: 4GB (SDHC Card) , the max. is up to 16GB
System: PAL or NTSC
Language: English

PH-855Mf 7 " Handsfree Monitor

Video Handsfree Monitor
Front panel: abs
Power In: DC15V
Screen: **Wide viewing angle**, Color- 7" TFT LCD Panel

Resolution: 1440H X 234V dot
Active Area: 154.08(W)x86.58(H)(mm)
View Angle: **Top**: 30deg.; **Bottom**: 60deg.
left / Right: 60deg.
Calling tone: Ding-Dong tone
Consumption: standby 70mA, operating 450mA.
wire: 4 wires + 2 power wires + 1 Video cable
The message LED flash if the call is from the 855CC or the Camera
Dimension: 220/320/40 mm
Packing: 0.6 cubic ft
Weight: 1.0 kg
need prebox
Prebox dimension: 220/310/50 mm



phase out

PH-855M7 7 " Handsfree color LCD Monitor

Video Handsfree Monitor
Front panel: abs
Power In: DC15V
Screen: **Wide viewing angle**, Color- 7" LED LCD Panel

Resolution: 1440H X 234V dot
Active Area: 154.08(W)x86.58(H)(mm)
View Angle: **Top**: 30deg.; **Bottom**: 60deg.
left / Right: 60deg.
Calling tone: Ding-Dong tone
Consumption: standby 70mA, operating 450mA.
wire: 4 wires + 2 power wires + 1 Video cable
The message LED flash if the call is from the 855CC or the Camera
Dimension: 235/150/25 mm
Packing: 0.5 cubic ft
Weight: 1.0 kg



new release

PH-855Mi 4 " Video Handsfree Monitor

4" Video Handsfree Monitor
Power In: DC15V
Screen: **Wide viewing angle**, Color- 4" TFT LCD Panel

Back light: White LED
Resolution: 960H X 234V dot
Active Area: 82.1(W)x61.8(H)(mm)
View Angle: **Top**: 10deg. **Bottom**: 30deg.
left / Right: 45deg
Calling tone: Ding-Dong tone
Consumption: standby 70mA, operating 300mA.
wire: 4 wires + 2 power wires + 1 Video cable
The message LED flash if the call is from the 855CC or the Camera
Wall mounting type
Material: ABS
Dimension: 170w/130h/35 mm
Packing: 0.3 cubic ft
Weight: 0.5 kg
3 kinds of different colors for choosing in side cover



PH-855Mh 4 " Video Handsfree Monitor

4" Video Handsfree Monitor
Power In: DC15V
Screen: **Wide viewing angle**, Color- 4" TFT LCD Panel

Back light: White LED
Resolution: 960H X 234V dot
Active Area: 82.1(W)x61.8(H)(mm)
View Angle: **Top**: 10deg. **Bottom**: 30deg.
left / Right: 45deg
Calling tone: Ding-Dong tone
Consumption: standby 70mA, operating 300mA.
wire: 4 wires + 2 power wires + 1 Video cable
The message LED flash if the call is from the 855CC or the Camera
Wall mounting type
Material: ABS
Dimension: 110w/113h/35 mm
Packing: 0.2 cubic ft
Weight: 0.4 kg
Option: prebox, Holder



phased out

PH-855MbR 3.5" Handsfree Monitor w/ Video Recorder

Video Handsfree Monitor
Power In: DC15V
Screen: Color- 3.5" Diagonal Color TFT LCD Panel

Resolution: 480H X 234V dot
Active Area: 72(W)x50.554(H)(mm)
View Angle: **Top**: 10deg. **Bottom**: 30deg.
left / Right: 45deg
Calling tone: Ding-Dong tone
Consumption: standby 70mA, operating 700mA
Wall mounting type
Material: ABS
wire: 4 wires + 2 power wires + 1 Video cable
Dimension: 130/280/45 mm
Packing: 0.3 cubic ft
Weight: 1.0 kg



phase out

Video Recorder

Video recorded with a device that is compatible with MPEG-4.(Linux format)
Resolution : 640*480 30FPS per second
Memory Card: 4GB (SDHC Card) , the max. is up to 16GB
System: PAL or NTSC

PH-855Mb HandsFree Monitor

Video Handsfree Monitor
Power In: DC15V
Screen: Color- 3.5" Diagonal Color TFT LCD Panel

Resolution: 480H X 234V dot
Active Area: 72(W)x50.554(H)(mm)
View Angle: **Top**: 10deg. **Bottom**: 30deg.
left / Right: 45deg
Calling tone: Ding-Dong tone
Consumption: standby 70mA, operating 450mA
Wall mounting type
Material: ABS
wire: 4 wires + 2 power wires + 1 Video cable
Dimension: 130/205/45 mm
Packing: 0.2 cubic ft
Weight: 0.7 kg



phased out

Language: English

PH-855M Handset Monitor

Power In: DC15V ~18V

Screen: Color- 4" Colour TFT LCD

Resolution: Color 960H X 234V dot

Calling tone: Ding-Dong tone

Consumption: standby 70mA, operating 600mA

Wall mounting type

Material: ABS

wire: 4 wires + 2 power wires + 1 video cable

The message LED flash if the call is from the 855CC or 855C7

Dimension: 220/195/50 mm

Packing: 0.3 cubic ft

Weight: 1.5 kg



PH-855Ma Handset Monitor

Power In: DC15V

Screen: Color- 4" Colour TFT LCD

Resolution: Color 960H X 234V dot

Calling tone: Ding-Dong tone

Consumption: standby 70mA, operating 600mA

Wall mounting type

Material: ABS

wire: 4 wires + 2 power wires + 1 Video cable

The message LED flash if the call is from the 855C5 / C7

Dimension: 210/225/55 mm

Packing: 0.3 cubic ft

Weight: 1.5 kg

phased out



PH-855CC The Control Center

This is the bridge between the Resident and VCP, pls refer to our Instruction Guide for the other functions.

Power In: AC100~230V Full Range

Decode: 20 call memory for 855CC

Review: Checking the last 20 call memories

Types: 1 to 10 Blocks

Dimension: 445/255/110mm

Packing: 1.3 cubic ft

Weight: 4.0 kg



5.6" LCD Panel for 855CC

The Monitor of 368CC

Working Voltage: Video- DC12V supply from 368CC

Installation way: Wall mounting type

Material: ABS

Dimensions: 160/180/38mm

Weights: 0.8kgs

Measurement: 0.3 cuft

phase out



PH-855Mg Audio HandsFree

Handsfree Audio Handset

Power In: DC15V

Calling tone: Ding-Dong tone

Consumption: standby 70mA operating 200mA

Wall mounting type

Material: ABS

wire: 4 wires + 2 power wires

The message LED flash if the call is from the 855CC or the Camera

Dimension: 210/95/40 mm

Packing: 0.2 cubic ft

Weight: 0.5 kg



PH-855M3 Audio handset

Power In: DC15~18V

Calling tone: Ding-Dong tone

Consumption: standby 70mA, operating 200 mA

Wall mounting type

Material: ABS

wire: 4-wire + 2 power wires

The message LED flash if the call is from the 855CC or the Camera

Dimension: 200/100/45mm

Packing: 0.2 cubic ft

Weight: 0.4 kg



PH-855Md Audio HandsFree

Handsfree Audio Handset

Power In: DC15V

Calling tone: Ding-Dong tone

Consumption: standby 70mA, operating 200 mA

Wall mounting type

Material: ABS

wire: 4 wires + 2 power wires

The message LED flash if the call is from the 855CC or the Camera

Dimension: 100/220/47 mm

Packing: 0.2 cubic ft

Weight: 0.5 kg

phase out



PH-P6 The power supply

Power In: AC110V/220V/230V

Power out: DC16.5-18V / 2.5A

Installation way: Wall mounting type

Material: ABS

Dimension: 160X120X80mm

Packing: 0.08 cubic ft

Weight: 2 kg

European design - Din Rail Type



PH-P9 Power Supply for Monitor

Power Source: AC 85-264V 47- 63 HZ

Working temperature -20 ~ +60 °C

Output: 15V, 0 ~ 5.0 A

DC output adjustment 15 ~ 16.5V

Dimensions: 170x97x40 mm

Net Weight: 0.6kg

Separated connectors AC / DC

When output LED indicator off: Fuse open



PH-P7a Switching Power Supply for Monitor

Power Source: AC100-240V 47-63HZ

Output: DC 15V / 1.5A

Installation way: Wall mounting type

Material: ABS

Dimensions: 105x55x36 mm

Net Weight: 115 mgs

Dual Purpose fixed way: European type of Din Rail or hangings type

Separated connectors AC / DC

When output LED indicator off: Fuse open

No need to dismantle from cover, you can change fuse easily

It's a convenient size (115 mg / 105x55x36 mm)

European design - Din Rail Type



PH-P8 Power Supply for Monitor

Power Source: AC 85-264V 47- 63 HZ
Working temperature -20 ~ +60 °C
Output: 15V, 0 ~ 5.0 A
DC output adjustment 14.25 ~ 16.5V
Dimensions: 170x97x40 mm
Net Weight: 0.6kg
Separated connectors AC / DC
When output LED indicator off: Fuse open



PH-855VSB Video/Signal Booster

Video/Signal booster
Power In: DC15~18V
Consumption: operating 200mA
Dimension:107Wx156Lx50Hmm
Packing: 0.03 cubic ft
Weight: 0.7 kg



PH-CSD System Distributor

Camera-system Distributor
Power In: DC15~18V
Consumption: Operating 300mA
Dimension: 107Wx156Lx50Hmm
Packing: 0.03 cubic ft
Weight: 0.7 kg



PH-VB4C Video Booster

For small space
one Video Main In
One Video Main Out
6 Branch output
Gain from 47 to 100 ohm
Power In: DC12~16V
Consumption: operating 100mA
Dimension: 35Wx26Lx6Hmm
Packing: 0.01 cubic ft
Weight: 0.1 kg



PH-NP Name Plate for Camera

For each kinds of cameras
Show resident's addresses or resident's numbers on it, visitors can call the resident who wants visit easily
Dimensions: the same as the dimensions of 855C7

